

Realtime T110 Access with Camera + ST10

Professional Fingerprint Access Control with Exit Fingerprint Reader



Specifications

Reader	Optical Fingerprint Reader, Dual Fingerprint Reader (Optional)
Proximity Card	EM, MIFARE Card (Optional)
Display	2.8" TFT True Color LCD
Keyboard	16 Keys (with backlight), 1 Door Bell Button
Interface	Power Port (9V - 12V; GND)
	TCP/IP, RS232/485, Wi-Fi (Optional)
	Wiegand 26/34 bits with 1 In & 1 Out
	Door Relay Output (COM;NO;NC)
	Duress Alarm Output (COM;NO;NC)
	Door Bell Button Input (PUSH; GND)
	Door Lock On/Off Input
	Door Bell Output
	Anti Pass Back Port (TXD, TXD, GND)
Camera	(Real Time Photo Taking)
TF Card (Micro- SD)	(Photo Storage)
Additional Feature	Reset Button
Temperature	-10°C - +60°C
Humidity	20% - 80%
Operation	One-way, Two-way, Multi Door/ Network
Registration Capacity	Normal: 1000FP/ 1000 Cards/ 1000
Passwords Authentication Methods	Fingerprint, EM Card, Password, Dual Fingerprint, Group Combination
Authentication Languages	English
Access Control	Able to control single door access through Wiegand, 50 time periods, Time setting authentication, Anti Pass Back, Sending attendance records by real time to Server or PC, Support Dual Fingerprint or Group Combination Authentication
Multi Door Access	5 Door Access Control (1 Door controlled by a Fingerprint Machine, 4 Doors controlled by 4 Fingerprint Readers connected by Fingerprint Machine through RS232/485)
Alarm	Force Removal Alarm, Duress Alarm, Force Door Open Alarm, Overtime Alarm
Auto Self-check	Yes
FAR/FRR	0.00001% / 0.1%
FP Verification Speed	1.0 s (with 2000 FP registration)
FP Verification Angle	0° - 360°
Smart FP Update	Yes



Features:

