# Realtime T32 with Camera

## Biometric with Camera Attendance RecorderA with Simple Access Control System

## Specifications

| | |
|---|---|
| Dimensions | L 198 x W 128 x H 43 (mm) |
| FRR | ≤0.01% |
| FAR | ≤0.0001% |
| FP Recognition speed | 1 sec |
| Capacity | 5000 pc |
| Transaction Memory Capacity | 200,000 |
| Images Installer | 25000 |
| Verification Modes | 1 : 1 OR 1 : N |
| Authentication Methods | FP, PIN, RFID, FP＋PIN, FP＋PIN＋RFID |
| Operation Mode | Standalone or connect with PC via LAN or WAN |
| Communications | RS232/485, TCP/IP, USB Drive, Wi-Gi, GPRS |
| Operation Power | <5W |
| Power Input | DC 12V |
| Weight | 1.2KG |
| Display | QVGA 76800 pixels color backlit LCD |
| Image Capture | Instant Photo-taking with built-in camera |
| Image Display | Support Image Retrieval & Display |
| Languages | English |
| Voice | English |
| Access control Feature | Standard with Time Zone Management |
| Attendance Checking | Any staff may check own attendance |

### Features:

| | | | |
|---|---|---|---|
| GPRS | USB Disk | Real Time Photo Taking | TCP/IP |
| Personal Identity Number | Backup Battery | Access Control | Wi-Fi |